



CARE INSTRUCTIONS

SURFACES SHOULD BE HANDLED WITH CARE TO AVOID DAMAGE FROM ABSORPTION, IMPROPER EXPOSURE, OR MECHANICAL IMPACT. SIMILARLY, MOVING PARTS SHOULD BE OPERATED GENTLY TO PREVENT EXCESSIVE WEAR ON FINISHED SURFACES AND HARDWARE.

MATTE WOOD FINISHES ARE ACHIEVED USING HIGH-SOLID POLYURETHANE PAINTS (18-20 GLOSS). GLOSSY WOOD FINISHES ARE OBTAINED THROUGH A BASE COAT PREPARED WITH POLYESTER RESIN-BASED PAINTS (SUCH AS POLYESTER PRIMER) AND FINISHED WITH DIRECT POLYURETHANE LACQUER > 90 GLOSS.

THE FINISH ON VENEERED OR SOLID WOOD IS ACHIEVED WITH ACRYLIC PAINTS, FREE OF FORMALDEHYDE AND HEAVY METALS, AND WITH HIGH CROSS-LINKING PROPERTIES (MEDIUM OPACITY OF 5 GLOSS).

FOR ROUTINE MAINTENANCE, CLEAN WITH A MICROFIBER CLOTH DAMPENED WITH WATER. IF NEEDED, USE ONLY WELL-DILUTED NEUTRAL SOAP IN WATER. AVOID CLEANERS CONTAINING ACIDIC AGENTS, SOLVENTS, ABRASIVES, AMMONIA, CHLORINE, ALCOHOL, OR DEGREASERS.

METAL COMPONENTS MAY HAVE ANODIZED OR EPOXY POWDER-COATED FINISHES, DEPENDING ON THE PRODUCT TYPE. FOR ROUTINE MAINTENANCE, CLEAN WITH A MICROFIBER CLOTH DAMPENED WITH WATER. IF NEEDED, USE ONLY WELL-DILUTED NEUTRAL SOAP IN WATER. AVOID CLEANERS CONTAINING ACIDIC AGENTS, SOLVENTS, ABRASIVES, AMMONIA, CHLORINE, ALCOHOL, OR DEGREASERS.

FOR ROUTINE MAINTENANCE OF GLASS SURFACES, USE A STANDARD GLASS CLEANER AND A MICROFIBER CLOTH. AVOID CLEANERS CONTAINING ACIDIC AGENTS, SOLVENTS, ABRASIVES, AMMONIA, CHLORINE, OR DEGREASERS.

EXTRAORDINARY MAINTENANCE OF DOORS AND THEIR COMPONENTS MUST BE CARRIED OUT BY QUALIFIED PERSONNEL. AVOID ANY MODIFICATIONS TO THE PRODUCTS THAT COULD COMPROMISE THEIR STABILITY.